

# **EZMarquee - 1 Line 40 Characters (Outdoor Sunlight)**

#### **1 Line 40 Characters - NEMA 4X**

The 1 Line 40 Char EZMarquee can hold up to a maximum of 40 characters (2") per line and features 1 line of RED/Tri-Color LEDs. EZMarquees are enclosed in NEMA 4X extruded aluminum housing with NEMA ICS 2-230 level of electrical noise immunity. All 1 Line 40 Character models are capable of communicating over RS232 and RS422/485 along with different models for Ethernet, DeviceNet and Profibus connectivity.

#### **Characteristics:**

Character Height: 2"
Characters per Line: 40
Number of Lines: 1
Visibility: 100"

#### 1 Line 40 Characters feature:

- 1 line of 40 characters max
- Pre-matched LEDs
- 24 Hour Burn-In tested
- International Character Set
- · Hang Mounting
- NEMA 4/4X Outdoor Housing
- NEMA ICS 2-230
- 110/220 VAC Power Input
- Surge Protection
- 100,000+ Hours Rated Life

See the different communication interface options available in the charts below

## 1 Line of 2", 40 Characters per line

**RED Outdoor** 

#### **RED Outdoor Highbright**

Model Number	Interface
EZMRH-1L40C-OUT	RS232 and RS422/485 only
EZMRH-1L40C-E-OUT	Ethernet included
EZMRH-1L40C-D-OUT	DeviceNet included
EZMRH-1L40C-P-OUT	Profibus included

### 1 Line 40 Characters



